

ROUGH OPENINGS FOR EXTERIOR DOOR UNITS

NON-WEATHERSTRIPPED UNITS WITH WOOD SILLS

CALL SIZE	UNIT TYPE	ROUGH OPENING	COMMENTS
2'8" x 6'8"	Single	34 1/2" x 84 5/8"	
3'0" x 6'8"	Single	38 1/2" x 84 5/8"	
4'0" x 6'8"	Double	51 1/8" x 84 5/8"	w/ T-Astragal
5'0" x 6'8"	Double	63 1/8" x 84 5/8"	w/ T-Astragal
5'4" x 6'8"	Double	67 1/8" x 84 5/8"	w/ T-Astragal
6'0" x 6'8"	Double	75 1/8" x 84 5/8"	w/ T-Astragal
2'8" x 6'8"	Single w/ 1-14" Sidelite	50 7/8" x 84 5/8"	w/ 2 1/4" Mull
3'0" x 6'8"	Single w/ 1-14" Sidelite	54 7/8" x 84 5/8"	w/ 2 1/4" Mull
3'0" x 6'8"	Single w/ 2-14" Sidelites	71 1/4" x 84 5/8"	w/ 2 1/4" Mulls
2'8" x 6'8"	Single w/ 1-32" Sidelite	68 7/8" x 84 5/8"	w/ 2 1/4" Mull
3'0" x 6'8"	Single w/ 1-36" Sidelite	76 7/8" x 84 5/8"	w/ 2 1/4" Mull
2'8" x 6'8"	Single w/ 2-32" Sidelites	103 1/4" x 84 5/8"	w/ 2 1/4" Mulls
3'0" x 6'8"	Single w/ 2-36" Sidelites	115 1/4" x 84 5/8"	w/ 2 1/4" Mulls

For 8'0" doors, use rough opening height of 100 5/8" on the above units.
For door units without wood sills, deduct 1 5/8" from the above heights.

WEATHERSTRIPPED UNITS WITH ALUMINUM SILLS

CALL SIZE	UNIT TYPE	ROUGH OPENING	COMMENTS
2'8" x 6'8"	Single	34 1/2" x 84 5/8"	
3'0" x 6'8"	Single	38 1/2" x 84 5/8"	
4'0" x 6'8"	Double	51 1/8" x 84 5/8"	w/ T-Astragal
5'0" x 6'8"	Double	63 1/8" x 84 5/8"	w/ T-Astragal
5'4" x 6'8"	Double	67 1/8" x 84 5/8"	w/ T-Astragal
6'0" x 6'8"	Double	75 1/8" x 84 5/8"	w/ T-Astragal
2'8" x 6'8"	Single w/ 1-14" Sidelite	50 7/8" x 84 5/8"	w/ 2 1/4" Mull
3'0" x 6'8"	Single w/ 1-14" Sidelite	54 7/8" x 84 5/8"	w/ 2 1/4" Mull
3'0" x 6'8"	Single w/ 2-14" Sidelites	71 1/4" x 84 5/8"	w/ 2 1/4" Mulls
2'8" x 6'8"	Single w/ 1-32" Sidelite	68 7/8" x 84 5/8"	w/ 2 1/4" Mull
3'0" x 6'8"	Single w/ 1-36" Sidelite	76 7/8" x 84 5/8"	w/ 2 1/4" Mull
2'8" x 6'8"	Single w/ 2-32" Sidelites	103 1/4" x 84 5/8"	w/ 2 1/4" Mulls
3'0" x 6'8"	Single w/ 2-36" Sidelites	115 1/4" x 84 5/8"	w/ 2 1/4" Mulls

For 8'0" doors, use rough opening height of 99 5/8" on the above units.

To determine the rough opening height for an exterior door unit with a transom, add the transom jam height plus 1 1/2" to the door unit rough opening height shown above. Custom size frames are available, rough opening information will be provided upon request.